

PA 440



Field Display for Current Loop with Contacts

Functional range

- ▶ free scalable display
- ▶ switch mode, hysteresis, parameterizable deceleration of the contacts
- ▶ no external power supply necessary

Product characteristics

- ▶ field display for pressure transmitter with output signal: 4 ... 20 mA / 2-wire or 0 ... 10 V / 3-wire
- ▶ 4-digit LCD display
- ▶ plastic housing
- ▶ pressure compensation element with PTFE-Filter

Optional versions

- ▶ IS-version
- ▶ 2 contacts
- ▶ 4-digit LED display

Typical application



in situ display at e.g. for tank batteries, pumping stations and much more.




Analogue signal	
Standard	2-wire: 4 ... 20 mA
Option IS-version	2-wire: 4 ... 20 mA
Option 3-wire	0 ... 10 V (in preparation)
Accuracy	$\leq \pm 0.1\% \text{ FSO} \pm 1 \text{ digit}$
Supply	
2-wire system	supplied by current loop; voltage drop $\leq 6.5 \text{ V}$ IS version: max. 28 V _{DC} (for combination with transmitter and PA 440)
3-wire system	display is supplied parallel with transmitter; V _S = 8 V _{DC} ... 36 V _{DC}
Contact	
Number, type	2 independent PNP open collector contacts
Switching performance	contact rating max. 125 mA, short-circuit resistant
Switching frequency	max. 8/sec
Delay time	0 ... 100 sec
Miscellaneous	
Electrical protection	reverse polarity protection (no damage, but also no function); electromagnetic compatibility (emission and immunity according to EN 61326); short-circuit protection
Ingress protection	IP 65
Display	4-digit, 7-segment LC display, range of indication -1999 ... +9999; accuracy 0.2 % ± 1 digit; standard: LC display, digit height 18 mm option: LED display, digit height 10 mm, red
Permissible temperatures	electronics / environment / storage: -20 ... 70 °C
Material display housing	plastic ABS, grey
Cable entries	cable gland M16x1.5 Polyamide, seals NBR, diameter range: standard 5 ... 10 mm
Atmospheric pressure compensation	pressure compensation element with PTFE filter
Terminal clamps	vertical clamps for stranded and solid wires up to 2.5 mm ²
Dimensions (height x width x depth)	80 mm x 120 mm x 57 mm
Weight	approx. 220 g
CE-conformity	EMC Directive: 2014/30/EU
Explosion protection (optionally)	
Approval AX15-PA 440	IBExU08ATEX1126 X zone 1: II 2G Ex ia IIB T4 Gb
Safety technical maximum values	U _i = 28 V _{DC} , I _i = 93 mA, P _i = 660 mW, C _i = 0 nF, L _i = 0 μ H
Ambient temperature range	from -20 °C to +70 °C
Wiring diagram	
Dimensions (in mm)	

© 2020 BD|SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

Ordering code PA 440

PA 440



Standard version									
	8	5	1						
Analogue output									
4 ... 20 mA / 2-wire				1					
intrinsic safety for zone 1 / 4 ... 20 mA / 2-wire				E					
customer				9					consult
Contact									
without contact				0					
2 contacts ¹				2					
Unit									
without ²				0					
bar				1					
mbar				2					
mH ₂ O				3					
%				P					
mA				A					
customer				9					consult
Label on display									
standard				1					
neutral				N					
customer				9					consult
Display									
LC display						C			
LED display						D			
Housing material									
plastic ABS							G		
Special version									
standard							0	0	0
overvoltage protection ³							1	0	1
customer							9	9	9
									consult

¹ only possible in combination with LED display

² the unit signs are loose-settled

³ not possible for IS version